BikeHub Premium 1/06

Double the number of parking spaces, safe and sound!

High quality, maximum safety and many well thought-out details make BikeHub Premium the benchmark for double-deck parkers.

| Article number | EAN | Width | Height | Depth |
|--|-----|---------|--|------------------------|
| 105600054 | | 1700 mm | 2340 mr | m 2350 mm |
| | | | Parking spaces | 6 |
| | | | Colour | Silver |
| | | | Base material | Steel |
| | | | Construction type | Screwed / assembly kit |
| | | | Parking style | To park |
| | | | Type of mounting | Floor mounting |
| | | | Bike spacing | 500 mm |
| | | | Tyre width | 55 mm |
| 23 9 9 9 9 | | 9 | | |
| The double-deck parker in a class of its own, setting standards in quality and safety. The robust, corrosion-protected steel cons- truction with aluminium support rails is suitable both for par- king facilities at your company or residential complex and for | | | options and ensure that even high-quality bicycles can be parked safely. The ergonomic lifting aid with gas pressure damper and the smooth-running carrier rail - extended at a distance of only 320 mm from the ground - ensure that even heavy bicycles can | |

permanent use in public spaces. It complies with DIN standard 79008-1 and has been tested by TÜV, which means that it is demonstrably barrier-free and childproof. Anti-theft devices according to standard specifications offer easily accessible locking

- +Space-saving parking due to double-decker use
- Low effort due to lifting aid with lift function +
- Optimised for theft protection and barrier-free +
- Optionally for one or two-sided wheel adjustment +
- Modularly expandable for row systems without any +problems

be parked without any problems. Suitable for tyre widths up to 55 mm. Lateral wheel distance according to DIN 79008-1 at least 500 mm.



