Bicycle racks

1156

Stable, well-shaped simplicity


Corrosion-protected steel construction with robust tubular hoops, three to ten parking spaces and space-saving height-offset. No assembly required.

Article number	EAN	Width	Height	Depth
105700007	4250366513423	1050 mm	405 mm	687 mm
			Parking spaces	6
			Colour	Silver
			Weight	14,60 kg
	An an An		Construction type	Welded / ready assembled
\mathcal{N}			Base material	Steel
11			Mounting type	On the floor
			Tyre width	55 mm
			Configuration	Two-sided
		/		
		1		AN









In the Hoop Parker 1000 bicycles and pedelecs park offset in height at a comfortable spacing between wheels of 350 mm or also double-sided on request to save valuable space. The parking space depth is approx. 1850 mm for single-sided parking, approx. 3200 mm for double-sided. Fast set up, without requiring assembly

or concreting, this model can create large and super-large bicycle parking facilities in front of schools, lecture theatres, stadiums, train stations, etc. – or in front of the pharmacy. Ground anchors and mounting brackets are sold separately.

- + Robust, corrosion-protected steel construction
- + Alternate high/low setting
- + Optional for single or double-sided bike parking
- + Row/series connection (with an even amount of spaces) and ground mounting possible
- + No assembly required

