


2506 XBF

Bicycle parking with the best recommendation

With its functional frame rests and steel eyelets, this free-standing bicycle leaning system also protects top-quality bicycles from damage and theft.

Article number	EAN	Width	Height	Depth
105700144	4250366514680	3000 mm	856 mm	944 mm





Parking spaces	6
Colour	Silver
Weight	51,00 kg
Construction type	Screwed / assembly kit
Base material	Steel
Mounting type	On the floor
Bike spacing	500 mm
Tyre width	55 mm
Configuration	One-sided
Positioning space depth	1850 mm



The striking detail of this free-standing bicycle parking system is the diagonal frame rest sheathed in signal red plastic. It protects every bicycle or e-bike against wanton or accidental wheel twisting and consequential damage to the rims. Integrated steel eyelets provide optimal theft protection. The spacing between hoops is generously laid out and ideal for bicycles with up to

55 mm wide tyres. Spacing is 500 mm or 540 mm for double-sided parking. The stanchion thus offers you or your employees, customers and guests the highest level of parking convenience. Optionally single or double-sided. Of course, the system is pre-fabricated for ground mounting and series connection. Ground mounting brackets included.

- + Free-standing, bolted tubular steel construction
- + Ample plastic-sheathed frame rests
- + Integrated eyelets for preventing theft
- + Prefabricated for row/series connection



Further information on our products and contact options at: www.wsm.eu/en.
No guarantee can be given for the completeness and correctness of the data and illustrations.